

# BASE MODEL SANDWICH UNIT

**Model: CRA93-10**

## 93" Standard Top Sandwich Unit Refrigerator with Solid Doors - 10 Pans

Heavy gauge #300 Series stainless steel top, stainless steel front and end panels, galvanized steel rear and grill and aluminum interior.  
**Certified under NSF-7 to maintain temperatures in 86°F ambient and designed to maintain NSF-7 temperatures in 100°F ambient.**



### Options and Accessories

(upcharge and lead times may apply)

|   |                             |
|---|-----------------------------|
| Drawers in lieu of doors                  | Stainless steel pan slides  |
| Drawer section above the condensing unit* | Expansion valve system      |
| Overshelves (single or double)            | Stainless steel shelves     |
| Condensing unit left or right             | Flat insulated night covers |
| Additional epoxy-coated steel shelves     | Remote models               |
| Automatic, electric condensate evaporator | Door locks                  |
| Exterior dial or digital thermometer      | Adjustable legs             |
| Rear-mounted cutting board                | Crumb catcher               |
| Stainless steel back and interior         | Front breathing             |

\*Drawer section above condensing unit holds (1) 12 x 20 x 6 pan

**Continental**  
 Refrigerator

Toll-Free: 800-523-7138  
 Phone: 215-244-1400  
 Fax: 215-244-9579

539 Dunksferry Road  
 Bensalem, PA 19020  
[www.continentalrefrigerator.com](http://www.continentalrefrigerator.com)

Project Name:

Model Specified:

Location:

Item No:

Quantity:

AIA #:

SIS #:

### Standard Model Features

#### REFRIGERATION SYSTEM

Performance-rated refrigeration system

Environmentally-safe R-134a refrigerant

Unique air flow distribution allows pan product to maintain 33° - 41°F

Automatic, energy saving, non-electric condensate evaporator

Non-corrosive, plasticized fin evaporator coil

Easily serviceable, slide-out condensing unit

#### CABINET ARCHITECTURE

2" non-CFC polyurethane foam insulation

Spring loaded, self closing doors

Magnetic snap-in door gaskets

Heavy-duty, epoxy-coated steel shelves

12" deep, full length nylon cutting board

Insulated lid

5" casters

Completely enclosed, vented and removable rear and side grills

Refrigerated door section above the condensing unit

#### MODEL FEATURES

(10) 1/6 size non-recessed pans, 4" deep

Interior hanging thermometer

Field rehingeable doors

**NOTE:** CRA models come standard with a door over the condensing unit. A drawer over the condensing unit is an option.

APPROVAL:

## Model Specifications

### DIMENSIONAL DATA

|   |                  |
|---|------------------|
| Net Capacity (cu. ft.)                            | 32 (906 cu l)    |
| 1/6 Size Pans (4" deep)                           | 10               |
| Width, Overall (in.)                              | 93 (2362 mm)     |
| Depth, Overall (in.)<br>(incl. handles & bumpers) | 36 1/16 (916 mm) |
| Depth, Cutting Board (in.)                        | 12 (305 mm)      |
| Height, Overall (in.) (incl. 5" casters)          | 42 (1067 mm)     |
| Shelf Area (sq. ft.)                              | 14.2 (1.3 sq m)  |
| No. of Shelves                                    | 6                |
| No. of Full Doors                                 | 3                |
| No. of Half Doors                                 | 1                |
| Interior Depth (in.)                              | 30 (762 mm)      |
| Interior Height (in.)                             | 26 (660 mm)      |
| Interior Height (in.) (above condenser)           | 12 1/2 (318 mm)  |
| Interior Width (in.)                              | 89 (2261 mm)     |

### REFRIGERANT DATA

|                             |      |
|-----------------------------|------|
| Condensing Unit Size (H.P.) | 1/2  |
| Capacity (BTU/Hr)*          | 4220 |

### ELECTRICAL DATA

|                                     |                     |
|-------------------------------------|---------------------|
| Voltage (int'l)                     | 115/60/1 (220/50/1) |
| Fans                                | 4                   |
| Total Amps (int'l)                  | 13.0 (8.4)          |
| 10 ft. Cord/Plug [attached] (int'l) | Yes (No)            |

### SHIPPING DATA

|                       |                  |
|-----------------------|------------------|
| Weight (lbs.)         | 605 (274 kg)     |
| Height - Crated (in.) | 43 3/4 (1111 mm) |
| Width - Crated (in.)  | 95 (2413 mm)     |
| Depth - Crated (in.)  | 47 (1194 mm)     |

\* Rating @ +25°F evaporator, 90°F ambient

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.



Equipped with one NEMA-5-15P Plug  
(varies by country)

# Continental

Refrigerator

Toll-Free: 800-523-7138  
Phone: 215-244-1400  
Fax: 215-244-9579

539 Dunkserry Road  
Bensalem, PA 19020  
[www.continentalrefrigerator.com](http://www.continentalrefrigerator.com)

Due to our continued efforts in developing innovative products, specifications subject to change without notice.



MADE IN THE U.S.A.

© Copyright 2014. Continental Refrigerator.  
A Division of National Refrigeration & Air Conditioning Products, Inc.

## Model Plan Views

