

Continental



Refrigerator

SLIDING GLASS DOOR DISPLAY REFRIGERATOR

Utilizing Environmentally Safe, CFC-free R-134a Refrigerant



2R-SGD

Standard Features

- Modern, State-of-the-Art Styling
- Performance Rated Refrigeration System Utilizing Environmentally Safe R-134a Refrigerant
- 3" Non-CFC Polyurethane Foam Insulation
- Self-Closing Doors
- Cylinder Lock in Each Door
- Automatic Electric Condensate Evaporator
- 5" Casters
- Heavy Duty, Epoxy-Coated Steel Shelves
- External Dial Thermometer
- Double-Pane, Tempered Sliding Glass Doors
- Fluorescent Interior Lighting

Standard (S/S Front, Aluminum End Panels & Interior
Suffix SA (S/S Exterior, Aluminum Interior
Suffix SS (S/S Exterior & Interior)

Optional Features & Accessories

- | | |
|--------------------------------------|---|
| • Half Door | • Extra Shelves |
| • Pass-Thru
(Glass One Side Only) | • Stainless Steel
Shelves |
| • Remote | • Digital Thermometer |
| • Shallow Depth | • Increased
Refrigeration
Systems |
| • Legs | |
| • Stainless Steel Case
Back | |



c





REFRIGERATOR

SPECIFICATIONS

DIMENSIONAL DATA

	2R-SGD	2R-SGD-PT
Net Capacity (cu. ft.)	48	48
Width, Overall (in.)	52	52
Depth, Overall (Incl. Hdls.) (in.)	34	36
Depth (Less Door(s) (in.)	32	32
Clear Door Width (in.)	19	19
Clear Full-Door Height (in.)	58 1/4	58 1/4
Clear Half-Door Height (in.)	27	27
Height, Overall (Incl. 5" Casters)	82 1/4	82 1/4
No. of Full Door(s)	2	4
No. of Half Door(s)	4	8
No. of Shelves	8	8
Shelf Area (sq. ft.)	40.8	40.8
Tray Slide Capacity (Half)	12 ea.	12 ea.
Tray Slide Capacity (Full)	24 ea.	24 ea.

REFRIGERATION DATA

	2R-SGD	2R-SGD-PT
Condensing Unit Size (H.P.)	1/2	1/2
Capacity (BTU/Hr)*	4010	4010

ELECTRICAL DATA

	2R-SGD	2R-SGD-PT
Cabinet Specifications	115/60/1	115/60/1
Feed Wires (Incl. Ground)	3	3
Condensing Unit Specs.	115/60/1	115/60/1
Total Amperes	13.6	14.3
Cabinet Amperes	4.1	4.8
Defrost Amperes	-	-
Power Supply Cord	yes	yes



SHIPPING DATA

	2R-SGD	2R-SGD-PT
Height – crated (in.)	81 1/2	81 1/2
Width – crated (in.)	55	55
Depth – crated (in.)	37	37
Volume – crated (cu.ft.)	97	97
Weight Std – crated (lbs.)	530	610
Weight SS – crated (lbs.)	610	680
Weight Std – uncrated (lbs.)	360	430
Weight SS – uncrated (lbs.)	440	510

* Rating @ +25°F Evaporator, 90° Ambient

Note: All specifications subject to change without notice.

Note: If the cabinet is located directly against wall and/or under low ceiling, a minimum clearance of 2" is required.



A Division of National Refrigeration & A/C Products, Inc.
 539 Dunksferry Road Bensalem, PA 19020
 (800) 523-7138 Fax: (215) 244-9579
 www.continentalrefrigerator.com