DESIGNER LINE WARMER

Model: DL1WE-PT



1-Section Extra-Wide Pass-Thru Warmer

DL1WE-PT - Stainless steel front, aluminum end panels and interior

DL1WE-SA-PT - Stainless steel exterior, aluminum interior

DL1WE-SS-PT - Stainless steel exterior and interior



Options and Accessories

(upcharge and lead times may apply)

Rehinging of doors (consult factory)
Special electrical req. (consult factory)
Correctional Facility Options
One way security screws
Locking hasp (lock not included)
Stainless steel mesh cover
Coverless hinges

Consult factory for other model configurations, options and accessories.

Model Specified:

Location:

Item No: Quantity:

AIA #: SIS #:

Standard Model Features

HEATING SYSTEM

Self contained, performance rated heating system

90°F to 180°F temperature range

Top mounted heating plenum "plug" with circulating fan

Unique air flow distribution ducts

CABINET ARCHITECTURE

3" non-CFC polyurethane foam insulation

Smooth, polished chrome workflow door handles

Cam action, lift off hinges

Self-closing doors

Magnetic snap in Santoprene™ door gaskets

Cylinder lock in each door

Heavy duty, chrome plated steel shelves

Heavy duty pilaster strips

Adjustable 6" stainless steel legs

MODEL FEATURES

Automatic interior lighting

Electronic controller with digital display & hi-low alarm

Stainless steel strip heaters located in base of interior



Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

APPROVAL:

Model Specifications

DIMENSIONAL DATA Net Capacity (cubic feet) 22 (623 cu I) Width, Overall (inches) 28 ½ (724 mm) Depth, Overall (inches) 38 ¾ (984 mm) Depth (inches) (less door) 32 (813 mm) Depth (inches) (door open 90°) 84 (2134 mm) Clear Door Width (inches) 21 ½ (556 mm)

Clear Door Height (inches)	58 5/8 (1489 mm)
Height, Overall (inches)	83 ½ (2115 mm)

Number of Doors 2 Number of Shelves 3

Shelf Area (square feet) 22.2 (2.1 sq m)

Tray Slide Capacity 19

ELECTRICAL DATA


Voltage	208-230/60/1
Feed Wires (including ground)	3
Total Amps (International)	7.2 (7.2)
Total Wattage @ 208-230 volts	1500
10 ft. Cord/Plug (International)	No (No)


SHIPPING DATA

Height - Crated (inches)	85 ½ (2172 mm)
Width - Crated (inches)	31 5/8 (803 mm)
Depth - Crated (inches)	42 (1067 mm)
Volume - Crated (cubic feet)	65 (1841 cu I)
Weight Std - Crated (pounds)	320 (145 kg)
Weight SS - Crated (pounds)	336 (152 kg)

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.

Model Plan Views





IMPORTANT NOTE: If the cabinet is located directly against a wall and/or under a low ceiling, a minimum clearance of 12" is required on top and 3" on sides and rear.



Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Due to our continued efforts in developing innovative products, specifications subject to change without notice.







© Copyright 2021. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.