## **DESIGNER LINE DISPLAY FREEZER**

Model: DL3F-GD



# 3-Section Display Reach-In Freezer with Hinged Glass Doors

DL3F-GD - Stainless steel front, aluminum end panels and interior

DL3F-SA-GD - Stainless steel exterior, aluminum interior

DL3F-SS-GD- Stainless steel exterior and interior



### **Options and Accessories**

(upcharge and lead times may apply)

Stainless steel case back	Casters
Additional epoxy coated steel shelves	Full doors
Chrome or stainless steel shelves	Special electrical req. (consult factory)
Rehinging of doors (consult factory)	Shallow depth (consult factory)
Pan slide assemblies	Pass-thru (consult factory)
Solid doors (consult factory)	Increased refrigeration system

Consult factory for other model configurations, options and accessories.

Project Name:		
Model Specified:		
Location:		
Item No:	Quantity:	

### **Standard Model Features**

SIS #:

#### REFRIGERATION SYSTEM

AIA #:

Self contained, performance rated "plug" refrigeration system

Environmentally-safe R-404A refrigerant

Refrigeration system is readily accessible on top of cabinet, separate from the "food zone"

Automatic, hot gas condensate evaporator

Expansion valve system

#### **CABINET ARCHITECTURE**

3" non-CFC polyurethane foam insulation

Triple-pane, tempered hinged glass doors

Chrome-plated handles

Cam action, lift-off hinges

Self-closing doors

Magnetic snap in door gaskets

Cylinder lock in each door

Heavy duty, epoxy coated steel shelves

Heavy duty pilaster strips

Adjustable 6" stainless steel legs

#### **MODEL FEATURES**

LED interior lighting

Top and side air distribution ducts

Automatic electric defrost

Cabinet upper side panels and refrigeration "plug" system can be removed and reinstalled at job site

Electronic controller with digital display & hi-low alarm



**Toll-Free: 800-523-7138** Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

APPROVAL:

# **Model Specifications**

DIMENSIONAL DATA	
Net Capacity (cubic feet)	72 (2039 cu I)
Width, Overall (inches)	78 (1981 mm)
Depth, Overall (including handles) (inches)	35 3/8 (899 mm)
Depth [less doors] (inches)	32 (813 mm)
Depth [doors open 90°] (inches)	55 ½ (1410 mm)
Clear Door Width (inches)	19 3/8 (492 mm)
Clear Door Height (inches)	58 % (1489 mm)
Height, Overall (including 6" legs) (inches)	83 ½ (2115 mm)
Number of Doors	3
Number of Shelves	12
Shelf Area (square feet)	71.4 (6.6 sq m)
Tray Slide Capacity	24 ea.
REFRIGERANT DATA	
Condensing Unit Size (H.P.)	2 ½
Capacity (BTU per hour)*	6050
ELECTRICAL DATA	
Voltage (International)	115/208-230/60/1 (220/50/1)
Feed Wires (including ground)	4
Total Amps (International)	22.5 (19.5)
Defrost Amps (International)	9.6 (4.8)
10 ft. Cord/Plug (International)	No (No)
SHIPPING DATA	
Height - Crated (inches)	85 ½ (2172 mm)
Width - Crated (inches)	90 (2286 mm)
Depth - Crated (inches)	42 (1067 mm)
Volume - Crated (cubic feet)	187 (5295 cu I)
Weight Std - Crated (pounds)	820 (372 kg)
Weight SS - Crated (pounds)	935 (424 kg)
Weight Std - Uncrated (pounds)	620 (281 kg)

Weight SS - Uncrated (pounds)

 $^{\star}$  Rating @ -15°F evaporator, 90°F ambient Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.

# Refrigerator

**Toll-Free: 800-523-7138** Phone: 215-244-1400 Fax: 215-244-9579

735 (333 kg)

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Due to our continued efforts in developing innovative products, specifications subject to change without notice.









© Copyright 2021. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.

## **Model Plan Views**





**IMPORTANT NOTE**: If the cabinet is located directly against a wall and/or under a low ceiling, a minimum clearance of 12" is required.